

G3/20 06054

research REPORT

WYLE LABORATORIES - RESEARCH STAFF TECHNICAL REPORT 66338-01

A DATA BASE AND ANALYSIS PROGRAM FOR SHUTTLE MAIN ENGINE DYNAMIC PRESSURE MEASUREMENTS APPENDIX C

DATA BASE PLOTS FOR SSME TESTS 902-214 through 902-314

bv

Thomas Coffin

A final report of work performed under contract NAS8-34343

for

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION GEORGE C. MARSHALL SPACE FLIGHT CENTER MARSHALL SPACE FLIGHT CENTER, ALABAMA 35812

January 1986


## **FOREWORD**

This report describes a dynamic pressure data base and data base management system developed to characterize the Space Shuttle Main Engine (SSME) dynamic pressure environment. The data base represents dynamic pressure measurements obtained during single engine hot firing tests of the SSME. Software is provided to permit statistical evaluation of selected measurements under specified operating conditions. interpolation scheme is also included to spectral trends with SSME power level. This report was prepared by Wyle Laboratories Scientific Services Systems Group for the National Aeronautics and Space Administration, George C. Marshall Space Flight Center. work was performed under NASA contract NAS 8-34343, entitled "Flow Dynamic Environments in High Performance Rocket Engines."


The author wishes to acknowledge the contribution to this study by Dr. G. Meares, Chief Architect of the data base management software described herein. Messrs. B. Dobbs and D. Duck contributed long hours over a digitizer pad to data base accomplish input. The singular value decomposition software for spectrum interpolation Mr. T. Nesman, MSFC technical developed by Dr. J. Jong. contract monitor, provided continuing support through informal project reviews and served as a focal point for definition of SSME data requirements.

## DATA PLOT LISTING FOR TEST STAND A2


Test	Channel Descriptor (Time History or PSD)	Maximum Frequency (Hz)	Time Slice (Sec)
214	MMC FUEL INJ PR	40,000	25 50 70 150 300 450 500 30 50
251	THRUST		10
252			
253 254			
255			•
256			
257			
258 259	·		
259 260			
261			
<b>262</b>			•
263			
264 265			
266			
267			
268			
269 270			
271			
276			
277			
279			•
283 284			
303			
306	1		
307			
310			
311 313			
314	<b>T</b>		




4 00 TN




4 00/IN





0. WG\ TN




T NOVIN


4 0017

10


. 9 19




0 100 > TN



F 00/EN



4 00 X EN



4 00 12

